#### **Geoscience Canada**

**Journal of the Geological Association of Canada Journal de l'Association Géologique du Canada**

### **Economic Geology Models 5. Specialty, Critical, Battery, Magnet and Photovoltaic Materials: Market Facts, Projections and Implications for Exploration and Development**

#### Laura Simandl, George J. Simandl and Suzanne Paradis

#### Volume 48, Number 2, 2021

URI:<https://id.erudit.org/iderudit/1081446ar> DOI:<https://doi.org/10.12789/geocanj.2021.48.174>

[See table of contents](https://www.erudit.org/en/journals/geocan/2021-v48-n2-geocan06355/)

#### Publisher(s)

The Geological Association of Canada

**ISSN** 

0315-0941 (print) 1911-4850 (digital)

[Explore this journal](https://www.erudit.org/en/journals/geocan/)

#### Cite this article

Simandl, L., Simandl, G. & Paradis, S. (2021). Economic Geology Models 5. Specialty, Critical, Battery, Magnet and Photovoltaic Materials: Market Facts, Projections and Implications for Exploration and Development. *Geoscience Canada*, *48*(2), 73–92. https://doi.org/10.12789/geocanj.2021.48.174

#### Article abstract

Many exploration companies are now focusing on specialty materials that are associated with so-called 'green technology'. These include 'battery materials', 'magnet materials' and 'photovoltaic materials', and many such commodities are also broadly labelled as 'critical materials' because they are seen as vital for industrial development, societal needs or national security. The definitions used for such materials are not always consistent among jurisdictions or across industry, and this paper attempts to clarify the criteria and address some common misconceptions. The distinction between major minerals (e.g. base metals) and 'specialty materials' (i.e. those mined or produced in much smaller amounts) is particularly important.

The markets for many specialty materials are growing faster than those for traditional ferrous, precious and base metals and they are often portrayed as excellent long-term investment opportunities. However, the small market bases for specialty materials and considerable uncertainty around growth projections (especially related to material substitutions and rapid technological change) need to be taken into consideration for objective assessment of the development potential of any proposed project, establishment of new supply chains by major corporations, and responsible decision-making (mineral policy) by government. In the short-term, projects aimed at specialty materials (materials with a small market base) cannot benefit from economy of scale, and their development hinges on commercially proven metallurgical processes, unless they are supported by governments or end-users.

Several specialty metals (e.g. germanium, indium, cadmium, and cobalt) are commonly obtained as by-product of base metal extraction. In such cases, systematic testing of base metal ores for their specialty metal content may justify the addition of relevant recovery circuits to existing smelters. If positive results are obtained, the need for targeting new sources of such specialty metals as primary exploration targets may be reduced or eliminated.

Where market conditions permit and concerns about the future availability of materials seem reliable, grass-roots exploration for specialty materials is warranted, and pre-competitive government involvement may be justified to promote such development efforts.

érudit

© The Geological Association of Canada, 2021 This document is protected by copyright law. Use of the services of Érudit (including reproduction) is subject to its terms and conditions, which can be viewed online.

<https://apropos.erudit.org/en/users/policy-on-use/>

#### This article is disseminated and preserved by Érudit.

Érudit is a non-profit inter-university consortium of the Université de Montréal, Université Laval, and the Université du Québec à Montréal. Its mission is to promote and disseminate research.

<https://www.erudit.org/en/>

# **SERIES**



Economic Geology Models 5. Specialty, Critical, Battery, Magnet and Photovoltaic Materials: Market Facts, Projections and Implications for Exploration and Development

Laura Simandl<sup>1</sup>, George J. Simandl<sup>2,3</sup>, and **Suzanne Paradis4**

*1 RDH Building Sciences Inc., Victoria, British Columbia, Canada*

*2 British Columbia Ministry of Energy, Mines and Low Carbon Innovation Victoria, British Columbia, Canada E-mail: George.Simandl@gov.bc.ca*

*3 School of Earth and Ocean Sciences, University of Victoria, British Columbia, Canada*

*4 Geological Survey of Canada Sidney, British Columbia, Canada*

#### **SUMMARY**

Many exploration companies are now focusing on specialty materials that are associated with so-called 'green technology'.

These include 'battery materials', 'magnet materials' and 'photovoltaic materials', and many such commodities are also broadly labelled as 'critical materials' because they are seen as vital for industrial development, societal needs or national security. The definitions used for such materials are not always consistent among jurisdictions or across industry, and this paper attempts to clarify the criteria and address some common misconceptions. The distinction between major minerals (e.g. base metals) and 'specialty materials' (i.e. those mined or produced in much smaller amounts) is particularly important.

The markets for many specialty materials are growing faster than those for traditional ferrous, precious and base metals and they are often portrayed as excellent long-term investment opportunities. However, the small market bases for specialty materials and considerable uncertainty around growth projections (especially related to material substitutions and rapid technological change) need to be taken into consideration for objective assessment of the development potential of any proposed project, establishment of new supply chains by major corporations, and responsible decision-making (mineral policy) by government. In the short-term, projects aimed at specialty materials (materials with a small market base) cannot benefit from economy of scale, and their development hinges on commercially proven metallurgical processes, unless they are supported by governments or end-users.

Several specialty metals (e.g. germanium, indium, cadmium, and cobalt) are commonly obtained as by-products of base metal extraction. In such cases, systematic testing of base metal ores for their specialty metal content may justify the addition of relevant recovery circuits to existing smelters. If positive results are obtained, the need for targeting new sources of such specialty metals as primary exploration targets may be reduced or eliminated.

Where market conditions permit and concerns about the future availability of materials seem reliable, grass-roots exploration for specialty materials is warranted, and pre-competitive government involvement may be justified to promote such development efforts.

#### RÉSUMÉ

De nombreuses sociétés d'exploration se concentrent désormais sur les matériaux spécialisés associés à ce que l'on appelle la « technologie verte ». Ceux-ci incluent les « matériaux pour batterie », les « matériaux magnétiques » et les « matériaux photovoltaïques », et de nombreux produits de ce type sont aussi largement étiquetés comme « matériaux critiques » car ils sont considérés comme vitaux pour le développement industriel, les besoins sociétaux ou la sécurité nationale. Les définitions utilisées pour ces matériaux ne sont pas toujours cohérentes entre les juridictions ou dans l'industrie, et ce document tente de clarifier les critères et de répondre à certaines idées fausses courantes. La distinction entre les principaux minéraux (par exemple les métaux de base) et les « matériaux spécialisés » (c'est-à-dire ceux extraits ou produits en quantités beaucoup plus faibles) est particulièrement importante.

Les marchés de nombreux matériaux spécialisés croissent plus rapidement que ceux des métaux ferreux, précieux et de base traditionnels et ils sont souvent présentés comme d'excellentes opportunités d'investissement à long terme. Cependant, le marché restreint des matériaux spécialisés et l'incertitude considérable entourant les projections de croissance (en particulier liées aux substitutions de matériaux et aux changements technologiques rapides) doivent être prises en considération pour une évaluation objective du potentiel de développement de tout projet proposé, l'établissement de nouvelles chaînes d'approvisionnement par les grandes entreprises et une prise de décisions responsable par le gouvernement (politique minière). À court terme, les projets visant des matériaux spécialisés (matériaux ayant un marché restreint) ne peuvent pas bénéficier d'économies d'échelle et leur développement repose sur des procédés métallurgiques commercialement éprouvés, à moins qu'ils ne soient soutenus par les gouvernements ou les utilisateurs finaux.

Plusieurs métaux spécialisés (par exemple le germanium, l'indium, le cadmium et le cobalt) sont couramment obtenus comme sous-produits de l'extraction des métaux de base. Dans de tels cas, l'analyse systématique des minerais de métaux de base pour leur teneur en métaux spécialisés peut justifier l'ajout de circuits de récupération adéquats aux fonderies existantes. Si des résultats positifs sont obtenus, la nécessité de cibler de nouvelles sources de ces métaux spécialisés en tant que cibles d'exploration primaires peut être réduite ou éliminée.

Lorsque les conditions du marché le permettent et que les craintes quant à la disponibilité future des matériaux semblent fiables, l'exploration primaire de matériaux spécialisés est justifiée, et la participation préconcurrentielle du gouvernement peut être justifiée pour promouvoir de tels efforts de développement.

*Traduit par la Traductrice*

#### INTRODUCTION

#### The Context of Critical Materials

Future growth in 'green technologies' is largely dependent on the anticipated increase in the use of electric vehicles, and the development of renewable energy operations and energy storage capacities in electricity grids. These visions of a 'green energy future' are indicated in recent studies by the World Bank Group (2017), Hund et al. (2020), the European Commission (2018, 2020), and Küpper et al. (2018). Green technologies are increasingly dependent on reliable supply chains of so-called 'battery', 'magnet', and 'photovoltaic' raw materials. Many of these raw materials are part of a broader category of materials commonly labelled as 'critical', although the criteria for this label are not always rigorous (see below). Efforts by major corporations and governments are underway to secure adequate supplies of several 'critical' raw materials, such as lithium (Li), cobalt (Co), nickel (Ni), graphite, vanadium (V), and manganese (Mn) to meet future demands. At the same time, there is growing public pressure to assess supply chains for such materials in terms of their human and/or environmental impacts, and to ensure that they meet ethical expectations held by western industrialized countries. The U.S., Japan, and many European countries have historically relied on materials sourced from Africa, China, South America, or other countries that have less stringent environmental regulations and lower production costs compared to those of western industrialized nations (European Commission 2017, 2020; World Bank 2017; U.S. Department of the Interior 2018; Hund et al. 2020; Fortier et al. 2020). This is one reason why traditional suppliers of raw materials such as Canada and Australia were finding it hard to compete with African, Chinese, and South American sources producing some of these materials.

The critical materials concept, which western countries relied upon during past military conflicts, was viewed as redundant by some western military powers after World War II and the Cold War, and their stockpiles of critical materials were eliminated or reduced. The rush for 'magnet' materials was reignited around 2010 by disruptions and insecurities around the availability of rare earth elements (REE), following the real or perceived threats by China to reduce or cut its REE exports to western-style industrialized countries as a bargaining strategy in geopolitical and economic negotiations (e.g. Simandl 2014; Goodenough et al. 2018). At that time, China controlled more than 95% of global REE production. Some REE are essential for the manufacturing of high-performance magnets used in wind turbines and electric-car drive trains, and they are widely used in portable computing and communication equipment (e.g. laptops, tablets, smart phones, etc.). These technologies are all considered essential for the economies and national security of developed countries, for efforts to reduce greenhouse gas emissions, and for the transition to low-carbon societies (European Commission 2017, 2020; World Bank 2017; Brainard et al. 2018; U.S. Department of the Interior 2018; Fortier et al. 2020; Hund et al. 2020). The rush to identify new REE resources quickly spilled over to other materials, including 'battery' and 'photovoltaic' materials, and a wide selection of so-called 'critical materials' are now attracting unprecedented exploration interest. The efforts to rely on responsible sourcing and the ongoing global coronavirus pandemic have not diminished this activity, because in many respects, they have highlighted the vulnerability of international supply chains for commodities of all types.

#### What Are Critical and Specialty Materials?

Numerous companies now focus and explore for materials that are deemed 'critical' by major industrialized nations or nation blocs (European Commission 2017, 2020; U.S. Depart-

ment of the Interior 2018; Fortier et al. 2020). A full list of these materials is provided in Table 1, which shows that designations vary among jurisdictions. In recent years, emphasis has shifted towards critical materials used in batteries and permanent magnets needed by electric vehicles, for electrical generation and for energy storage associated with alternative (renewable) sources (e.g. solar and wind energy). Most of these socalled 'battery', 'magnet', and 'photovoltaic' materials are designated as critical (Table 1), but many are also termed 'specialty materials' because their global production does not exceed 200,000 tonnes per year.

It is also important to remember that the usage of a given material in battery, magnet, or photovoltaic applications accounts for only a *portion* of its global annual production. For example, global natural graphite production for 2020 was reported at 1.1 million metric tonnes (Olson 2021), but only some of this is used in battery applications. Natural graphite is also used for applications such as refractory bricks, crucibles and crucible linings, brake linings, lubricants, and in electric arc furnaces. Similarly, most of the 86,000 metric tonnes of vanadium produced was used as an alloying agent in iron and steelmaking (Polyak 2021), and almost all the 18.5 million tonnes of manganese produced was used in the steel industry. Other uses of manganese include fertilizers, animal feed, and as a brick colourant, so its actual consumption for battery applications is a trivial part of the global production (Schnebele 2021). The low ratio between total global reserves for a given material and its yearly global production has been used for many years as a general indicator of potential future short-term resource shortages and related price hike forecasts, and as justification for increasing exploration efforts and expenses. This ratio is provided in Table 2. In interpreting data in this way, it is important to remember that ongoing exploration and mining activities continually define new reserves and upgrade resources to reserves, so these apparent 'resource lifetimes' are changing continuously. In a 1999 article for the 'Economist' (Anonymous 1999), Don Huberts (the head of Hydrogen division of Royal Dutch Shell) is quoted: "*The stone age did not end because the world ran out of stones, and the oil age will not end because we run out of oil*." His prophecy is becoming a reality, and the same will probably apply to materials that we currently consider as essential for a green economy.

The first purpose of this paper is to define and describe the terms 'critical', 'specialty', 'battery', 'magnet', and 'photovoltaic' materials as used today. We then highlight the importance of understanding the current market bases, various market projections, and the possible influences of technological change on future demand. It is especially important to separate hard data (including the current market base) from market projections subject to uncertainties. Both should be considered differently from documents containing more speculative or potentially inflated expectations regarding the commercialization of early laboratory research, non-technical documents emphasizing the potential future importance of a given material, and promotional documents aiming to attract speculative investment. We also stress the need to consider the effects of potential material substitutions and future technological devel-

opments on market projections of all types. A full appreciation of all these concepts is essential for the selection of exploration targets, the design of exploration programs, and the timing of mineral development projects or property acquisitions. These issues are important beyond the corporate world, as they should also influence responsible government-level decision making.

#### Definitions of key terms

Some key terms used in this paper require definition because they also have wider common usage that is less restrictive. Our definitions are provided below:

*Material:* the element, constituent, or substance (solid, liquid, or gas) of which something is composed of, or can be made of (may be organic, mineral, metal, etc.). Consequently, 'material' is a more general term than 'mineral' or 'metal' (see below).

*Mineral:* a solid, homogeneous crystalline chemical element or compound that results from the inorganic processes of nature (e.g. quartz, feldspar, fluorite, native gold, etc.). This term also includes industrial minerals. *Industrial Mineral:* a geological material, which is mined for its commercial value, but is not used for its energetic value or as a metal ore. Industrial minerals are valued for their physical and/or chemical properties (e.g. graphite, fluorite, barite). This term also includes 'industrial rocks' (e.g. marble, quartzite, and phosphate rock).

*Metal:* any of various opaque, fusible, ductile, and typically lustrous substances that is a good conductor of electricity and heat, forms cations by loss of electrons, and yields basic oxides and hydroxides (e.g. Cu, PGE, Au). For the purposes of this paper, it also includes some elements that are technically labelled as semi-metals (metalloids) by chemists (e.g. silicon, boron, germanium, and arsenic). For example, silicon has most of the metallic properties, aside from ductility; however, the term 'silicon metal' is used in many publications.

Some materials (e.g. magnesite) have dual allegiance. Magnesite can be considered as an industrial mineral if it is used in the production of Mg-bearing compounds valued for their physical and chemical properties. However, it is considered a metal ore when it is used as a raw material for the production of Mg metal.

#### MAJOR COMMODITIES AND SPECIALTY MATERIALS: IMPLICATIONS OF CONTRASTING MARKET SIZES

#### Example of Major Commodities: Base and Precious **Metals**

Exploration companies typically target major commodities such as ferrous metals (e.g. Fe and Mn), precious metals (e.g. Au and Ag), and base metals (e.g. Al, Pb, Ni, and Zn). These major commodities have well-established global market bases with relatively predictable growth rates related to global eco**Table 1.** 'Critical', 'specialty', 'battery', 'magnet', and 'photovoltaic' materials. A material is designated as a 'specialty' material if its global production is less than 200,000 tonnes per year (global production estimates are provided in Table 2). A material is classified as a 'U.S. Critical Material' if it was included in the U.S. Department of the Interior (2018) Critical Material List. Similarly, a material is classified as 'EU Critical Material' if included in the European Commission (2020) Critical Materials List. Materials are referred to as 'battery', 'magnet', and 'photovoltaic' based on prevalent use in trade journals, company reports, and government publications (by consumers, exploration companies, banks, general public, and governments). Note that individual platinum group elements (PGE) and rare earth elements (REE) are not listed individually.



nomic cycles. Production of major commodities is not severely geographically restricted and overall, their markets are subject to the law of supply and demand. The prices of these major commodities fluctuate, but there are always markets for the production of most of them, with 'spot prices' available through metal exchange(s).

For these major commodity materials, assuming that technical aspects (e.g. geological, geotechnical, mineralogical, metallurgical factors) are favourable, and that societal and economic conditions permit, a given deposit can generally be developed. It is also normally the case that if we consider two hypothetical and technically identical deposits having the same

ore-grade, the deposit having greater tonnage is more likely to be developed than the smaller deposit. This is because economy of scale leads to cost efficiency, as the cost per unit of output generally decreases with the increasing scale and lifespan of the operation.

The positive effects of the economy of scale for many industrial commodities with well-established market bases (e.g. Cu and Fe) are demonstrated by currently profitable high-tonnage, low-grade deposits that are exploited at high production rates.

An example of a mining operation benefiting from economy of scale is the Highland Valley porphyry copper–molybdenum mine in British Columbia, with proven and probable reserves of 484 Mt at 0.31% Cu and 0.007% Mo, respectively. Resource estimates are as follows; measured: 552.3 million tonnes at 0.29% Cu and 0.008% Mo; indicated: 861.6 million tonnes at 0.23% Cu and 0.009% Mo, and inferred: 270.5 million tonnes at 0.20% Cu and 0.008% Mo. The forecasted 2020 production from Highland Valley was 120,000–125,000 tonnes of Cu, and 1500–1800 tonnes of Mo (Clarke et al. 2021). The Highland Valley operation will be used in the next section as a benchmark in discussion of importance of the market base constraint on development of specialty metal deposits.

#### Examples of Specialty Materials

In contrast to the major commodities and construction materials, many other materials, including some perceived as 'critical,' are produced in much smaller quantities. Materials that have global production below 200,000 tonnes/year are commonly referred to as 'specialty' materials (Tables 1 and 2).

The size of the global market for a typical specialty material, in terms of tonnage, is less than the annual Cu production of two deposits comparable in size to the Highland Valley mine summarized above. Consequently, mining operations supplying specialty materials do not benefit from economy of scale in the manner that large deposits of major commodities enjoy. An example is tantalum (Ta; global production of 1700 tonnes; Table 2), for which some medium-sized operations may be mechanized, whereas smaller and higher-grade deposits, especially if located in developing countries, are artisanal enterprises, worked by hand (Mackay and Simandl 2014; Simandl et al. 2018). Tantalum is a material of great importance in high-technology applications, but its small market base and current prices provide limited incentive for the development of new high tonnage, low-grade deposits that would have to rely on the economy of scale to be profitable. However, there are exceptions, such as pegmatite mining operations in Australia where Ta is co-produced with Li, and where companies are vertically integrated or have long-term contracts for their output.

The REE provide another example. In the medium- and long-term, there is high expected market growth for some of the REE, especially for Nd and Dy, and the market conditions appear very promising. However, let us put this into the context of the *current* market situation. If the law of supply and demand applies and no punitive import tariffs or export restrictions exist, one or two hypothetical, newly developed

deposits each producing 50,000 tonnes/year of rare earth oxides (REO) would result in a short-term market oversupply. This is because the world REO demand, including yttrium (Y), was estimated at only 250,000 tonnes in 2020 (Gambogi 2021a, b). It is not surprising that most of the REE deposits that were investigated as potential non-Chinese sources of REE in the early 2000s never made it to the production stage. The price of a specialty material can be severely impacted by oversupply from a single potential new source.

In contrast, a hypothetical new Cu mine equivalent to the Highland Valley example would represent only a small fraction (approximately 0.6%) of the global 2020 Cu production, estimated at 20 million metric tonnes (Flanagan 2021; Table 2). The impact of a new Cu mine on the global supply of Cu would be minimal, and no short-term oversupply of Cu would emerge.

Examples of specialty metals that are considered critical by the U.S. Department of the Interior (Fortier et al. 2020) and the European Commission (2020) include both Ta (used in capacitors), and certain REE, mainly Nd and Dy (used in highintensity permanent magnets). Other critical specialty materials include minor alloying agents for steel alloys (e.g. Nb, Ta, W, and Be), and other metal alloys (e.g. Sc).

To summarize, we can say that under normal (free market) conditions, projects targeting specialty materials cannot be assessed in the same way as those targeting major commodities. At least in the short-term, because of the small market bases, potential specialty material producers cannot compensate for lower grades by mining and processing larger tonnages of ore (i.e. relying on economies of scale) unless the specialty material is a by-product or a co-product of another commodity. However, if the specialty material is also considered critical, as discussed in the next section, free market conditions may not apply, because in some cases financial incentives may be provided by governments or major corporations.

#### CRITICAL MATERIALS

#### Concepts and Definitions

The concept of critical materials is familiar to most people in the resource sector, and there are several examples and reviews of how materials are assessed and ranked in terms of criticality (e.g. U.S. Department of Defense 2013; European Commission 2014, 2017; Simandl et al. 2015; Hayes and McCullough 2018).

Raw materials are essential to the global economy and society. Availability of some materials at competitive prices is now important for the high technology industry and the development of clean emission-free energy. During World War II and the subsequent Cold War, most western countries identified critical materials and maintained stockpiles of them. 'Critical material lists' were considered to be obsolete following the disintegration of the Soviet Union in the late 1980s, and stockpiles were reduced. However, since the early 2010s, relationships between the United States and other western countries with China and Russia have deteriorated, so many western industrialized countries re-established lists of materials



**2020 World Lifetime of**



http://www.geosciencecanada.ca

 $\overline{a}$ 



**Table 2.** *Concluded*

https://doi.org/10.12789/geocanj.2021.48.174

deemed as critical for economic, environmental, or national security reasons.

Since 2010, critical materials lists of western industrialized countries have been updated and expanded. For example, the 2018 list commissioned by the U.S. Department of the Interior contains 35 materials (Table 1). The lists of critical materials become substantially longer if the PGE and REE are considered as discrete chemical elements, rather than as groups of elements that commonly occur together. Depending on the interests of the organization that commissions the study (e.g. European Commission, U.S. Departments of Defense and of the Interior and Energy; see reference list for sources), the list of critical materials will vary significantly (Simandl et al. 2015; Hayes and McCullough 2018; see Tables 1 and 2).

The methods used to establish critical materials lists also vary (Simandl at al. 2015) and are not always exclusively based on usage and demand. The methodology used in several wellknown criticality studies was compared by Simandl et al. (2015) and thirty-two criticality studies were discussed and summarized by Hayes and McCullough (2018).

Figure 1 demonstrates the principle behind a traditional criticality study, as applied by the European Commission (2014). The vertical axis represents the increasing risk of supply disruption, and the horizontal axis represents the increasing economic importance of a given material. The vertical and horizontal dotted lines represent acceptable 'economic' and 'supply risk' thresholds. For simplicity, we selected two industrial minerals (barite and graphite), one metal (Cu), and one construction material (aggregate). Barite exceeded the supply risk threshold of the study, but its economic importance was low. Copper and aggregate exceeded the economic threshold but were considered at low risk of supply disruption. However, natural graphite exceeded both thresholds and is thus defined as a critical material. The European Commission's critical material study emphasized the importance of materials to their economy, but other studies may employ different criteria. For example, the horizontal axis could represent importance to national security or other specific policy objectives.

Several nations that are major exporters of raw materials have produced their own critical materials lists, which may not always follow the reasoning outlined above, and may reflect internal or regional political pressures. These lists commonly combine the EU and U.S. critical material lists, which reflects the desire to export to the EU and/or the U.S., and to support development of their own non-critical resources. For example, on March 11, 2021, Canada released its own list, which includes 31 materials (Government of Canada 2021). This list of 31 materials includes Cu, which is excluded from U.S. and EU critical material lists, and also includes Nb, U and potash. Canada is itself a major producer of these four commodities, so it is not vulnerable to high supply risks for any of these materials. There is nothing legally wrong with the creation of such 'expanded criticality lists', but the original meaning of the term 'critical' is lost or distorted. The inclusion of Nb, Cu, U, and potash simply reflects the importance of these commodities to Canada's resource-based economy and Canada's desire to supply its trading partners and allies.



**Figure 1.** Criticality concept. The vertical axis represents the increasing risk of supply disruption and the horizontal axis represents the increasing economic importance of a given material. The vertical and horizontal dotted lines represent acceptable 'economic' and 'supply risk' thresholds. For simplicity, and to highlight the versatility of this approach, we selected two industrial minerals (barite and graphite), one metal (copper), and one construction material (aggregate). Barite exceeded the supply risk threshold of the European Commission (2014) critical material study; however, its economic importance was low. Copper and construction aggregate exceeded the economic threshold but were considered at low risk of supply disruption. Only natural graphite exceeded both thresholds and plotted in the critical materials field. The horizontal axis of the 2014 European Commission's critical material study represented importance to the economy.

Any critical mineral list that lacks description of the methodology on which it is based should be examined closely to avoid misinterpretation, because some critical mineral list entries may be motivated more by domestic efforts to preferentially support mineral production than by true risk of supply disruption.

To reduce the supply risk, some governments are encouraging the development of domestic critical material-bearing deposits and related supply chains via financial or other incentives. This approach may result in the development of deposits that would not otherwise be developed in a free trade environment. Governments in industrialized countries may also mitigate the level of supply risk by expanding strategic stockpiles of critical materials to limit the impact of potential supply disruptions. This would represent a shorter-term solution but might in some cases be more convenient and cheaper than encouraging development of a domestic supply.

#### Resources, Reserves and Supply Chains

The concept of a 'circular economy' (defined as a regenerative approach benefiting industries, society, and the environment through ethical mining and recycling) was recently embraced by most industrialized nations and major corporations (e.g. Nassar 2017; Merli et al. 2018). It is expected to influence the classification of critical materials by improving or fortifying existing supply chains. Industry, investors, and the general public are acutely aware that potential shortages in critical materi-

als may materialize in the short to medium terms. However, they seldom realize that the supply chain beginning with an exploration project and leading to end-use of any material (Fig. 2) is complex and not easy to quantify. The supply chain involves exploration, development, mining, processing, concentration, refining, and end-product manufacturing. It extends beyond the production period as end-of-chain activities (by-product recovery, recycling, and mine rehabilitation) must now also be considered for any project.

If all critical material projects currently in the exploration and development stages targeting materials belonging simultaneously to the critical and specialty material categories were brought to production as scheduled, there would be a shortterm oversupply, which would inevitably affect prices. The problem that most exploration companies and investors struggle with is how to screen and rank critical material projects according to their true merit.

In general, after the discovery of a major commodity deposit, the development of mining infrastructure, milling facilities and concentration circuits is routine and rarely technically insurmountable. However, for many critical materials (e.g. REE, graphite, Ta, Co, and Li) varied and complex mineralogy can present metallurgical challenges in processing, which can impede the development of a deposit (Fig. 2). This is especially problematic if the critical material *also* belongs to the specialty materials category, because the research investment and financing of new or complex extraction circuits is not justified for such a small market base.

If we consider the simple ratio of global reserves to yearly commodity production (lifetime of reserves; Table 2), shortages of critical materials appear unlikely. This ratio is only an indicator of order of magnitude, but Table 2 shows that at the 2020 production rates, the present global reserves (*sensu* USGS) for most critical materials would last from 12 to more than 100 years. Global reserves will also grow with continued exploration to replace mined-out deposits and upgrade subeconomic resources to reserves. The most likely causes of critical materials shortages would be weaknesses (e.g. bottlenecks) in other links of the supply chain (Fig. 2), time lags in reaching production, or the unwillingness of consumers to accept higher prices. The resistance of consumers to the use of materials sourced from jurisdictions or operations with questionable environmental or human rights records may also become more important in the  $21<sup>st</sup>$  century.

#### BATTERY MATERIALS

#### Transportation Applications

With recent positive forecasts for electric vehicle market growth, the term 'battery materials' has emerged as a strong promotional label in the exploration industry. The term generally refers to Li, Co, Mn, V, Ni, and graphite. It disregards several materials used in lead–acid, nickel–cadmium (NiCd), nickel–metal hydride (NiMH), and other older battery technologies. The term also disregards materials used in batteries that are currently in research development, and/or were recently introduced. Examples of excluded materials are Pb, Cd, sul-



**Historic** 

**Waste** 

**Tailing and** 

and Refining

**Figure 2.** The supply chain from deposit exploration to manufacturing of the endproduct and its use. The orange boxes are particularly relevant to this paper and for the early technical ranking of the deposit according to their development potential. In the early stages, only the general market base and growth projections, conceptual and early exploration data, and preliminary metallurgical/refining (geometallurgical) information are available.

Recycling

phuric acid and certain REE (mainly La, Ce, and Y), which may account for 4 to 18 wt.% of NiMH batteries (Lin et al. 2016). The 2020 global production of these materials is provided in Table 2.

Battery technologies are rapidly evolving, but the current emphasis in transportation-related applications is on lithiumion batteries. A typical modern Li-ion battery consists of an anode, a cathode, an electrolyte, a polymer separator, Cu and Al current collectors, and a casing. The anode electrode consists mainly of graphite and/or other carbon-based materials. The most common type of cathode electrode belongs to a 'layered category' of  $LiMO<sub>2</sub>$ , where M consists of a combination of Co, Ni, Al, and/or Mn. 'Non-layered categories' of cathodes (e.g. lithium iron phosphate,  $LiFePO<sub>4</sub>$ , also referred to as LFP) are less common. LFP-type batteries were used mainly in China for bus propulsion, grid stabilization, and in some electric vehicles. Until recently, it was believed that LFP batteries would be replaced by batteries relying on layered cathodes, mainly nickel–manganese–cobalt (NMC) and nickel–cobalt– aluminum oxide (NCA) types that possess higher energy densities (e.g. Olivetti et al. 2017). A high energy density battery is favoured in transportation applications because it provides a longer travel range for the electric vehicle between two consecutive charges for the same weight of battery. Surprisingly, since October 2020, lower energy density LFP batteries are finding their way into Tesla Model 3 vehicles produced in China and into lower-cost electric vehicles produced elsewhere. Research and development objectives specific to Li-ion batteries for the automotive industry are summarized in Figure 3. This figure, modified from Bresser et al. (2018), combines views of representatives from China, Germany, Japan, and the U.S. who participated in the Advanced Lithium Batteries for Automobile Applications 10 Conference held in Chicago, U.S. in 2017. It is essentially a survey summary and it provides a comprehensive overview of the research and development strategies in several industrialized countries. The details vary by jurisdiction, but the long-term objectives are similar, i.e. manufacturers aspire

**End Product** 

Manufacture

and Use



**Figure 3.** Summary of research and development objectives specific to batteries for the automotive industry; covering anode, electrolyte and cathode materials. The anticipated progression in anode materials (black) leads from graphite to lithium in the long term. Similarly, in terms of electrolyte progression (green), the expected path will lead from liquid organic electrolytes to solid polymer/inorganic electrolytes. The expected cathode evolution trend (purple) leads from current lithium– iron–phosphate (LiFePO<sub>4</sub>; i.e. LFP) and NMC to sulphur (orange) in the long term. Post-lithium–ion battery era shown in blue will be dominated by metal–sulphur and metal–air batteries. The proportions of metals, in respective order, are indicated numbers in parenthesis. NMC = nickel–manganese–cobalt (for example, NMC 111 has Ni–Mn–Co in ratios of 1:1:1). NCA = nickel–cobalt–aluminum (Ni–Co–Al) oxide. This figure is based on selected presentations from the annual International Conference on Advanced Lithium Batteries for Automotive Applications held in Chicago in October 2017 and is modified from Bresser et al. (2018).

to reach the post-Li-ion battery era through the commercialization of new battery chemistries. During this process they wish to increase the safety and energy density of batteries and reduce the use of costly cobalt. Inevitably, such successes would change the material requirements for the industry.

Substitutions are being routinely explored to reduce the use of high-cost raw materials in batteries (Leader et al. 2019), and especially those listed on EU and U.S. critical material lists. These efforts aim to protect industrial end-users against the impact of supply disruptions and keep the prices of batteries as low as possible without sacrificing quality or efficiency. The requirements for Li, Co, Ni, Mn, and C materials to produce lithium–cobalt oxide (LiCoO<sub>2</sub>; LCO), lithium–nickel–cobalt– aluminum oxide  $(LiNi<sub>0.8</sub>Co<sub>0.15</sub>Al<sub>0.05</sub>; NCA)$ , and nickel–manganese–cobalt oxide (NMC) battery cathodes are listed in Table 3, in units that reflect their energy density (kg of material per kilowatt-hour). The lower requirement for Co in NCA and NMC cathode types is quite evident, as is the implied sensitivity of different types to changes in the prices of individual battery materials. Conversely, the variety in compositional proportions allows some flexibility of cathode choice, depending on commodity prices.

As an example, the direct impact of a hypothetical 100% increase in the price of Li, Co, Mn, and Ni on the overall cost of Li-ion batteries is shown in Figure 4. In the case of Mn, doubling the price has a limited impact, regardless of the battery type. In the case of Ni, the impact would be low to mod-

**Table 3.** The main materials required for production of five prototypical cathodes used in Li-ion batteries in kg/kWh (Olivetti et al. 2017). LCO = lithium-cobalt oxide; NCA = lithium–nickel–aluminum oxide; NMC = lithium–nickel– manganese–cobalt oxide (where numbers following 'NMC' designation represent Ni:Mn:Co ratios on a mole fraction basis; for example, NMC 622 has a 6:2:2 Ni:Mn:Co ratio).

	Li	Co	Ni	Mn	
<b>LCO</b>	0.113	0.959	$\left( \right)$		$\sim$ 1.2
<b>NCA</b>	0.112	0.143	0.759		
<b>NMC 111</b>	0.139	0.394	0.392	0.367	
<b>NMC 622</b>	0.126	0.214	0.641	0.200	
<b>NMC 811</b>	0.11	0.094	0.750	0.088	

erate for NCA and NMC 811 types. On the other hand, Co price increases would be severe for LCO and NMC 111 types but would not affect lithium–manganese oxide  $(LiMn<sub>2</sub>O<sub>4</sub>)$ LMO) or LFP systems. Lithium price increases would have the most significant effect on LFP and LMO batteries but would affect all types to some extent (Fig. 4).

Nevertheless, the cost of raw materials is only one of many factors that need to be considered in this sector. For example, NMC 811 batteries show great promise in efforts to increase the driving range of electric vehicles and reduce the use of Co. However, technical problems and especially safety concerns around thermal runaway (leading to fires) have impeded the penetration of NMC 811 batteries into North American and European markets. Adamas Intelligence estimated that between January and September 2019, the market share of new passenger electric vehicles equipped with NMC 811 batteries increased from less than 1% to 18% in China but reached only 7% globally (Green Car Congress 2019).

In theory, solid-state batteries will be less expensive, will benefit from higher energy densities, and will provide higher safety than 'traditional' liquid electrolyte-based batteries currently used in plug-in electric vehicles. However, the potential impact of specific future battery chemistries for electric vehicles (Fig. 3) is difficult to evaluate because many of these are in the early research stage and have yet to demonstrate commercial viability. Expectations of usage remain speculative, and some predictions may be overly optimistic (Sapunkov et al. 2015; Walker 2018).

#### Energy Storage Applications

Stationary energy storage systems are required to maintain the stability of the electric power grids during transient peak demands and to accommodate the intermittent nature of renewable energy generating power systems (e.g. wind and solar). They are also important for backup power generation in a carbon-neutral future. The requirements for these uses are different from those that apply to transportation applications (Guney and Tepe 2017; Mendoza-Vizcaino et al. 2019). Low energy density is not a major issue for stationary energy storage systems, but safety, reliability and durability are important (Chediak 2018). Although there is a perception that Li-ion batteries will be more important in transportation rather than in



Figure 4. Impact of  $100\%$  price increase in Li, Co, Mn, and Ni on the cost of selected Li-ion battery systems (from Leader et al. 2019).

energy storage, this may not be the case. Bloomberg's predictions suggest that by 2030 the U.S. energy power grid storage capacity will approach 80 GWh (Fig. 5) and that Li-ion batteries will play a major role in this achievement (Chediak 2018).

Examples of non-Li energy-storage systems that already have reached the market or have the potential to do so include vanadium redox flow (VRFB), lead–acid, nickel–cadmium (NiCd), nickel–metal hydride (NiMH) types, and high-temperature batteries such as sodium–sulphur (NaS) and sodium– nickel–chloride (NaNiCl) types (Luo et al. 2015). Vanadium redox flow batteries appear particularly promising, but require an ion exchange membrane made from *Nafion*, which is an expensive product from DuPont (Vanýsek and Novák 2017).

In recent years, VRFBs have been considered as front-runners in grid-scale energy storage and to be on the verge of commercialization (Sánchez-Díez et al. 2021). However, a lifetime cost analysis of nine electricity storage technologies in twelve different system applications suggests that this is far from certain (Schmidt et al. 2019). Large-scale repurposing of used batteries from electric vehicles or traditional batteries displaced by solid-state batteries in other sectors could represent alternatives to VRFB deployment (Miao et al. 2019). Batteries operating at temperatures around 300°C, such as sodium–sulphur (NaS) and sodium–nickel–chloride (NaNiCl) are effective for energy storage, but the need to maintain a high temperature and related safety concerns currently present obstacles to commercialization.

The U.S. Department of Energy's Global Energy Storage Database (Sandia National Laboratories 2021) currently contains 1697 energy storage projects (proposed, under construction, operational or decommissioned). Battery technologies included as operational or future operations in this database include Li-ion (e.g. lithium iron phosphate, lithium titanate, lithium manganese dioxide, lithium nickel cobalt aluminum oxide), Na-ion batteries (e.g. sodium nickel chloride), redox flow batteries (e.g. vanadium), hybrid flow batteries (e.g. zinc bromine), and Ni-ion batteries (e.g. nickel iron, nickel metal hydride, nickel cadmium). Consequently, many materials that are currently not considered to belong to the 'battery' category may become more important in the future, and the demand for some materials of current interest could diminish. The potential for technological developments in the energy storage sector resembles the situation in the transportation sector (Fig. 3) and the long-term directions of both are hard to predict.

#### MAGNET MATERIALS

The term 'magnet materials' presently refers largely to the REE, specifically neodymium (Nd), praseodymium (Pr), samarium (Sm), dysprosium (Dy), and terbium (Tb). It also includes Co, but omits materials used in older magnet technologies such as ferrite-type magnets. Developments in permanent magnet technologies were slow and steady over more than 50 years (Baker 2018). Aluminum–nickel–cobalt (AlNiCo) magnets were first developed in the 1940s. In the 1950s, inexpensive, easy-to-process, relatively demagnetization-resistant ferrite or ceramic magnets (e.g.  $BaFe_{12}O_{19}$  and  $SrFe_{12}O_{19}$ ) were introduced. More powerful REE-based magnets started with the development of  $YCo<sub>5</sub>$  magnets and later  $SmCo<sub>5</sub>$  and  $Sm<sub>2</sub>Co<sub>17</sub>$  magnets then captured most of the market in high-performance motors.  $Sm_2Co_{17}$  magnets were then



**Figure 5.** Expected growth in the total U.S. energy storage capacity in gigawatthours according to Chediak (2018). Values are forecasts from 2018 onwards.

largely replaced by  $Nd_2Fe_{14}B$  magnets, due in part to research following the eightfold increase in Co prices caused by civil unrest in the Democratic Republic of the Congo (then called Zaire) in 1978 (Baker 2018). This is a prime example of how material price instability can drive technology research.

Neodymium–iron–boron (NdFeB) magnets contain approximately 30% REE, mostly Nd and to a lesser extent Dy (the latter is added to widen the operating temperature range), and small concentrations of other REE (e.g. Pr). Today, they are highly publicized because of their use in motors for electric vehicles, wind turbines and a variety of portable electronic equipment, and are considered to have the greatest potential market growth. Currently, REE (mainly Nd and Dy) represent 8% of the total cost and 50% of the raw materials cost for a typical electric vehicle motor (Fig. 6; Hummel et al. 2017; Delfeld 2018). According to Roskill (2018), a typical electric vehicle now requires around 1 to 2 kg of Nd–Pr alloy.

Price variations of Nd and Dy have a much higher impact than comparable price variations of Cu, steel, or Al, and will affect the total cost of a typical electric vehicle motor module (Fig. 6; Hummel et al. 2017). If we assume that the price of an electric motor used in the Chevrolet Bolt vehicles produced in 2017 was U.S. \$1375 (middle of the range estimate provided in Fig. 6), the price of Nd and Dy raw materials would have been approximately U.S. \$110, or about 8%. If the cost of Nd and Dy doubles, the total price of the motor would increase from U.S. \$1375 to U.S. \$1595. The REE would then account for 13.8% of the electric motor costs for the vehicle.

In 2018 and 2019, approximately 30% of the world's wind turbines relied on direct drive NdFeB magnet-based technology. The construction of these turbines accounted for 8–9% of estimated global NdFeB magnet production. In the future, proposed offshore wind farms are expected to compete headon against the growing demand for NdFeB magnets for use in electric vehicles (Roskill 2019). To achieve the U.S. Department of Energy's objective of generating 86 GW of electric power from U.S. offshore wind farms by 2050, approximately 15,500 tonnes of Nd would be required. If the average Nd requirement for an electric vehicle motor is conservatively assumed to be 0.75 kg per vehicle, the amount needed for offshore wind energy purposes equates to nearly 21 million hybrid or electric vehicles (Fishman and Graedel 2019).

For these reasons, and because of perceived risks in global REE supply, research is seeking substitutes for NdFeB mag-



Figure 6. Cost breakdown of an electric motor for an electric vehicle; specifically, a Chevrolet Bolt E-Motor. Cost of motor reported to be U.S. \$1200–1550. Source: Hummel et al. (2017). Note that values in left pie chart do not sum to 100% likely due to rounding.

nets (Widmer et al. 2015; Pavel et al. 2017a, b) and methods to recycle REE from waste (Schulze and Buchert 2016; Auerbach et al. 2019; Swain and Mishra 2019). If the REE cannot be eliminated, the REE content of magnets could also be reduced through better design and use of nanocomposites (Geuss 2018). Over the past decade, lots of research was directed towards improving the microstructure and physical properties of non-REE-based permanent magnets. Those with the best potential for replacing REE-based permanent magnets (or at least filling the gap between ferrite and REE-based magnets) were covered in detail by Cui et al. (2018). These details are well beyond the scope of this paper; however, as is the case for the battery industry, future technological innovations leading to commercialization results of this research could significantly alter the market conditions for materials currently belonging to this category.

Selecting the best choice among permanent magnet technologies is not straightforward if costs, performance, energy use, environmental impact and other aspects are all taken into consideration (Grunditz et al. 2018). The SmCo-type magnets are weaker and more costly (at current prices) than their NdFeB counterparts, but they can operate at higher temperatures than NdFeB magnets. Despite their shortcomings, unheralded old-technology ferrite magnets still account for the largest portion of the permanent magnet market by volume. Permanent magnets are also not an *absolute* requirement for electric vehicles, as some use so-called induction motors. The latter rely on current flowing through the stator windings to induce a magnetic field, and thus require no permanent magnets. However, motors using permanent magnets are lighter and smaller than induction motors and provide faster acceleration and longer driving ranges. Tesla, a premium North American electric car manufacturer, employs both permanent magnets and induction motors. In the past, its Model S and Model X vehicles used induction motors, whereas its Model 3 motor relied on permanent magnets (Geuss 2018). However, since 2019, all three Tesla models use motors with permanent magnets rather than induction motors to increase their range and performance.

#### PHOTOVOLTAIC MATERIALS

Theoretically, solar energy could provide more than enough energy for Earth's population (Solar Energy Industries Association 2018). Recent improvements in photovoltaic (PV) technology have reduced the cost of solar energy relative to traditional energy sources. The power capacity of installed PV panels in the U.S. reached 60 GW in 2018, and it is expected to double by 2023. China's total PV capacity recently increased by 60 GW in only one year (Solar Energy Industries Association 2018), and the cumulative global capacity of photovoltaic installations reached an energy generating capacity of 518 GW in 2018 (Heath et al. 2020). Thus, photovoltaic technology is a major contributor to efforts to combat climate change through green energy, and materials used in these applications are attracting wide interest.

Before the early 1970s oil crisis, most of the efforts to recover energy from solar radiation were focussed on aerospace applications (Braga et al. 2008). The oil crisis first ignited interest in the terrestrial application of photovoltaic technology. Silicon-based and 'thin-film' photovoltaic technologies are described separately below, but both are expected to remain important in the quest to optimize efficiency in converting solar energy into electricity. Ultimately, both technologies may be combined in the production of highly efficient multi-junction cells. However, currently this gain in efficiency is counterbalanced by a significant increase in manufacturing complexity and production cost.

#### Silicon-based Photovoltaic Technology

Until 1996, production of silicon-based photovoltaic (PV) technology was focused on panels using monocrystalline silicon (where the crystal lattice of a given photovoltaic cell is continuous, unbroken, and free of grain junctions and boundaries). Since then, there has been a shift to so-called 'polycrystalline panels' (where individual cells consist of multiple small crystals or grains of silicon in contact with each other and having varied crystallographic orientations). Both types are siliconbased, and raw materials used in their production until around 1997 largely came from rejects provided by the microelectronics industry (Braga et al. 2008). Today, most commercial PV modules based on first-generation silicon wafer technology convert 17% of incoming solar energy into electricity (Green et al. 2015; Fraunhofer Institute for Solar Energy Systems 2020). The theoretical efficiency of a crystalline silicon solar cell is around 29% (Richter et al. 2013), and efficiencies approaching these limits are reported for prototype designs (Oberbeck et al. 2020).

The raw materials used to produce metallurgical grade and chemical grade silicon metal are readily available, but these cannot be used directly in the production of solar grade silicon because of impurities or unfavourable physical properties. Silica raw material generally contains less than  $99.8\%$  SiO<sub>2</sub> and must be upgraded. The transformation involves carbothermic reduction (Xakalashe and Tangstad 2011; Maldonado 2020) followed by chemical or metallurgical processing to yield silicon metal at  $\geq$  99.9999% Si. The latter has a price of U.S. \$10/kg or more, compared to less than 5 cents/kg for raw silica. Processing is energy-intensive and without government interventions, solar grade silicon prices would likely be U.S. \$70/kg (Louwen et al. 2016; Chigondo 2018). There is much ongoing research to find lower-cost methods to produce solargrade silicon (e.g. Marchal et al. 2015; Darghouth et al. 2021; Nagahata et al. 2021).

#### Thin-film Photovoltaic Technology

The relatively high prices of crystalline silicon also motivated research into 'thin-film-technology' solar cells that require one or more specialty metals. These are widely regarded as having a promising role in future PV technology.

These thin-film PV cells commonly involve cadmium–tellurium (CdTe), copper indium gallium selenide (CIGS), or other materials such as zinc oxide (ZnO) and cadmium–sulphur (CdS). Since about 2010, the conversion efficiency of these thin-film modules has increased significantly (Green et al. 2015; Fraunhofer Institute for Solar Energy Systems 2020). For example, the conversion efficiency of CdTe modules has increased from 9% to 19% since 2010. The future of the photovoltaic industry appears bright because modern high concentration multi-junction thin-film photovoltaic cells achieve conversion efficiencies of up to 47.1% in laboratory tests (Fraunhofer Institute for Solar Energy Systems 2020). This is considerably above the theoretical limits for silicon-based PV cells.

Many of the raw materials involved in thin-film PV technology are largely co-products of base metal smelting, so they are not ideal primary exploration targets. Many believe that material shortages or potential future supply disruptions could slow down commercialization of new technologies for energy production, and the availability of each metal should be considered individually (Davidsson and Höök 2017; Frenzel et al. 2017; Zhou et al. 2020).

Research in the thin-film technology domain is as intensive (if not more intensive) than in the field of crystalline silicon cells. The future of thin-film-based panels is very promising from a technological standpoint. However, some of them contain materials considered toxic (e.g. Cd), so questions linger regarding environmental impacts during production and later recycling and/or disposal.

In summary, if we consider that the need for renewable energy will continue to rise rapidly and that, based on the laboratory tests, the modern multi-junction photovoltaic cells can achieve conversion efficiencies exceeding 47%, the future of the photovoltaic industry appears bright.

#### RELATIONSHIPS BETWEEN SPECIALTY, BATTERY, MAG-NET, AND PHOTOVOLTAIC MATERIALS

Up until this point, we have presented definitions and examples of critical, battery, magnet, photovoltaic, and specialty materials. Some of these materials belong to more than one of these five material categories; the complex relationship between these categories is depicted in Figure 7 and it shows many overlaps. For example, Co belongs to all categories except for photovoltaic materials. Cobalt can be promoted as a critical battery and/or magnet material depending on the available fundraising opportunities, or the availability of government stimuli. In contrast, barite only belongs in the wider critical materials category, so promotional opportunities for barite are far more limited. Figure 7 also shows that many critical materials fit into the specialty materials category. Projects that target critical specialty materials are severely constrained by the limited market base. As discussed earlier in the paper, such projects are unlikely to benefit from the economy of scale that commonly applies to the production of major commodities. In the final section of the paper, we examine some of the specific challenges and problems that must be considered in the assessment of projects targeting critical specialty materials.

#### FUTURE EXPLORATION AND DEVELOPMENT OF SPECIALTY MATERIALS

#### The Distinction Between Market Base and Market **Projections**

Larger exploration companies and vertically integrated mining companies have the luxury to consider medium- and longterm investments, but many junior mining and exploration companies are more concerned with short-term survival. Regardless of the company's size and financial situation, the market base (i.e. tonnes of material used per year) must be reflected in the design of exploration programs, and in the selection of a viable target. For example, in the short-term, compensating for low-grade ore in a specialty material(s) deposit by attempting to define much larger reserves is probably not a viable strategy because the current market base cannot support a large operation with a high production rate. However, if projections of the future demand for the material are enticing, lower grade–higher tonnage deposits may be appropriate targets for long-term development planning. This would be particularly true for an established specialty material producer with an existing market share.

#### Assessing Long-term Projections in Relative and Absolute Terms

In the long term, the markets for battery, magnet, and photovoltaic specialty materials are expected to grow at much faster rates than markets for typical industrial metals, such as Al and Cu. We are all bombarded by market projections and development proposals for battery, magnet, and photovoltaic materials, but most of the better studies are proprietary in nature. For the purpose of this paper, we use projections from the World Bank Group study authored by Hund et al. (2020). These projections predict the potential magnitude of the energy material requirements for the year 2050, assuming the "2-degree scenario" from the International Energy Agency (2017) report on energy technology perspectives. This scenario is considered to have at least a 50% chance of limiting the average global temperature increase to 2°C by the year 2100. The market growth projections for 17 materials considered in this scenario can be presented in two contrasting ways (Fig. 8a, b). Essentially, materials historically targeted by exploration companies because of their significant market base, such as Mn, Cu, Zn, Al, Mo, Pb, and Ni, are forecast to benefit from modest



**Figure 7.** Examples of overlapping material categories. Terms 'battery', 'magnet', and 'photovoltaics' are used here in *sensu lato* (as used by industrial users, exploration companies, banks, and government organizations). For example, cobalt (Co) is currently considered as one of the specialty materials but may be referred to as a 'critical', 'battery', or 'magnet' metal.

growth. This contrasts with the predictions for other materials belonging to the specialty material category, which are expected to benefit from spectacular growth. For example, Li, Co, and In have 2050 annual demand forecasts for energy technologies that are at least double their total production estimated for 2018 (Fig. 8a; Table 2).

Any promoter trying to raise money for critical materials, battery materials, or photovoltaic materials exploration projects will be thrilled by the approach used in Figure 8a, because the projected 2050 market for graphite, Li, Co, In, V, Ni and Nd appears spectacular relative to the corresponding 2018 global productions. Such long-term market growth projections, presented alone, or briefly as presentation slides, could impress explorationists, investors and developers, and might alarm politicians and end-users of such critical materials. However, if the same data are presented in a more traditional way, i.e. in terms of absolute yearly consumption (Fig. 8b), investor enthusiasm might subside, as the projected energy industry consumption (tonnage/year) for most materials with substantial market bases (e.g. Al, Cu, Zn, and Mn) is relatively unappealing, and usage projections for specialty materials (e.g. Ti, Nd, V, Li, and Co.) appear small in absolute terms. The only material that stands out regardless of the way in which the data are presented is graphite, although the projections for Ni also indicate significant market growth. The most balanced view of these long-term projections is achieved if both approaches (Fig. 8a, b) are presented simultaneously to allow comparison.

#### The Accuracy of Market Projections

Market projections are available for most specialty materials, but such projections have often proved inaccurate. For example, a projection for 2014, made in 2010, estimated a total





**Figure 8.** Expected material demands based on projections for ten energy technologies in 2050, assuming a 2 degrees scenario as defined in the International Energy Agency (2017) report; a) shown as a percentage of 2018 global production; b) shown in millions of tonnes. The 2018 global production data is from USGS Mineral Commodity Summaries (U.S. Geological Survey 2021). Figure modified from Hund et al. (2020).

demand of 197,000 tonnes/year for Rare Earth Oxides (REO) (Watts 2010) and even higher estimates were given by several renowned mineral economists. However, in 2018 the REO demand was still only 190,000 tonnes/year (Gambogi 2020). Only in 2019 did market growth exceed the 2014 projection made by Watts (2010), and 2019 production was estimated at 220,000 tonnes/year (Gambogi 2021a). The accuracy of the current market projections will probably be much better than that of historical projections. This is largely because government stimuli, if and when enacted, will support the development of dependent technologies and supply chains, which will provide a greater sense of security for potential explorationists and developers.

#### Direct Impact of Market Base on the Design of Exploration Programs

Some specialty metals (e.g. REE, Nb, Ta and Li), are commonly considered to be primary exploration targets. Projects targeting these materials should be compared and ranked in the early stages because only a small fraction of projects that seem to satisfy development requirements will actually achieve production. Projects may meet most requirements related to mining, metallurgy, infrastructure, and societal license, but they are unlikely to be economically viable under open-market conditions if the market base is small.

Several specialty metals projects were explored for many years before the mineralogical and metallurgical constraints on development were fully appreciated. It is economically difficult for specialty metal operations to justify the development and use of complex custom-designed metallurgical circuits instead of established systems that are commercially available. Thus, REE-bearing ionic clays, REE-fluorocarbonates, and REEphosphates will continue to be favoured as REE ore minerals because commercial metallurgical circuits for them already exist (Mariano and Mariano 2012; Simandl 2014). This is not the case for unusual minerals such as REE-bearing silicates, which are present in many such exploration projects, including some that are enriched in more desirable heavy REE. Essentially, high-grade, metallurgically simple, near-surface deposits will be favoured because of the lower associated development and mining costs relative to larger deeply buried, metallurgically complex, or lower-grade deposits. The costs to bring large tonnage, low-grade deposits into production cannot be justified for materials with a small market base, and high research and development costs to tackle metallurgical complexities are difficult to justify for small operations.

The limited market base for specialty materials restricts the short-term interest of major mining companies in these commodities. However, there are some exceptions. Most of them are related to potential by-products that can be recovered in smelting. For example, Ge, In, and Cd are recovered at Teck Resources' integrated Zn and Pb smelting and refining complex in Trail, British Columbia, as by-products. In 2021, the Rio Tinto Fer et Titan (RTFT) complex in Sorel (Quebec) started operating a small plant aiming to produce 20% of the global demand for scandium (Sc) oxide, which is presently approximately 15 tonnes/year. This initiative was supported with financial contribution from the Quebec government. Other large companies are aware of upcoming opportunities, and many may pre-emptively attempt to establish themselves in promising specialty materials markets.

Some major companies are now showing long-term interest in materials that currently have a modest market base but have relatively well-constrained market projections - for instance, Li. Regardless of which battery technologies eventually dominate the electric automotive industry, Li demand is expected to grow substantially over the next few decades. However, as with most specialty metals, early screening of the project is necessary to determine if it really has a future. Lithium projects currently in production or reaching an advanced stage of exploration or development can be subdivided into 3 main categories: (1) evaporite/brine derived; (2) hard-rock pegmatite deposits consisting predominantly of spodumene (LiAl $Si<sub>2</sub>O<sub>6</sub>$ ); and (3) unconventional sources such as jadarite  $[(LiNaSiB<sub>3</sub>O<sub>7</sub>(OH)]$  and related Li- and B-bearing clays (Kesler et al. 2012; Evans 2014). Possible development of jadarite deposits in the Jadar Basin of Serbia is currently being investigated by Rio Tinto as a source of both Li and B (Gourcerol et al. 2019), and if successful, could significantly impact the global Li market.

#### Industry's Ability to Ensure Availability of Critical **Materials**

Great progress is being made in developing exploration models and in customizing existing exploration methods for the discovery and development of most of the critical materials listed in Tables 1 and 2, including those associated with batteries, magnets, and photovoltaic technologies. Traditional geochemical and geophysical surveys, as well as remote sensing methods used for other target types, can be applied in the exploration for most primary critical materials. However, these well-established methods must be modified and their applications customized to maximize their effectiveness. Detailed discussion covering new developments in exploration methods for individual critical materials is outside the scope of this paper, but progress in exploration methods specific for carbonatite-related deposits (including critical materials such as REE, Nb, and fluorite) illustrate some of the trends (Simandl and Paradis 2018).

Similar efforts are also taking place to develop methods for the extraction of complex, difficult to decompose minerals. For instance, examples of numerous flow sheets for REE projects are tabulated in Verbaan et al. (2015). Most of REE are currently derived from REE-bearing fluorocarbonates (e.g. bastnaesite and synchysite) and REE-bearing phosphates (e.g. monazite and xenotime); however, these minerals contain dominantly light REE. Most heavy REE are obtained from ion-adsorption clay deposits and this is expected to continue in the near future (Simandl 2014; Borst et al. 2020). The ability to extract REE from complex zirconosilicates (e.g. eudialyte) and other heavy REE-enriched minerals commercially at competitive cost would be a major breakthrough. It could permit production of heavy REE from large deposits hosted by alkaline intrusions whose development is presently impeded by metallurgical challenges.

Some specialty material(s) are present in high concentrations in small and/or uncommon deposits. For example, Ge is enriched in Kipushi-type polymetallic deposits in the Democratic Republic of Congo (Höll et al. 2007) and In-bearing polymetallic veins exist at the Akenobe deposit in Japan (Schwarz-Schampera 2014). However, exploration for such 'unusual' deposits as the primary target is not recommended if these metals can instead be recovered as by-products of other metal extraction operations. For example, Ga, Ge, and In are all by-products of Zn smelting (Schwarz-Schampera 2014; Paradis 2015), and rhenium (Re) is recovered from molybdenite concentrates produced from porphyry Cu–Mo type deposits (Millensifer et al. 2014). Cobalt has diverse associations as a coproduct from the Katanga Copperbelt Cu ores (central Africa) and is present in many magmatic Ni and Cu deposits, and in Ni–Co laterites (Roberts and Gunn 2014).

Current Cu, Pb, Zn, and Ni mines and waste piles from historical operations may contain significant resources of these metals. Analyzing and evaluating these potential sources of critical materials is recommended over any attempt to generate material-specific exploration projects. Should shortages of these by-product specialty metals develop, adding appropriate extraction circuits to operating smelters that currently do not recover these elements may be the most straightforward solution, assuming that suitable economics and grades prevail. Higher-than-normal concentrations of a desired specialty metal (e.g. Ge in a Zn deposit) may also positively affect the development potential of such a deposit by subsidizing the production of its primary commodity.

#### **SYNOPSIS**

Projects involving 'battery', 'magnet', photovoltaic, and/or 'critical' materials currently have favourable public, government, and shareholder perceptions that make them easier to promote than projects aimed at more traditional major commodities. They are commonly seen as essential in the quest for a future carbon-neutral society. However, the assessment of projects involving specialty materials is far more complex and uncertain than the evaluation of projects involving major commodities that exploration and mining industries are accustomed to.

The influence of the market base is the most important parameter in the assessment of specialty materials exploration programs by industry, but it is also the most commonly overlooked or disregarded aspect. Careful consideration of the market base is also crucial for informed decision-making by government agencies seeking to support or encourage such projects. In the case of a given specialty material, only the best exploration and development projects will be economically successful without government or end-user stimuli. Early ranking of projects with an emphasis on grade and tonnage, geometallurgy, and infrastructure is recommended so that exploration budgets can be assigned to the best projects, and potential government stimuli responsibly allocated. In the short term, the economy of scale should not be expected to play an important role in the development of any projects targeting specialty materials because of their limited market base. However, in the medium and long term, the concept of economy of scale might become applicable to some of these projects because of fast market growth projections for some commodities. The reliability and accuracy of such growth projections are uncertain, especially in the light of rapid technological change.

Clearly distinguishing between current market data, legitimate market projections, and inflated expectations of new technologies by scientists and engineers is essential in order to separate factual information from more speculative or promotionally oriented viewpoints, and to make wise investment decisions. There are many uncertainties to consider in the rapidly changing world of modern technology. The greatest of these are the potential impact of future technological innovations (which are virtually unpredictable), future material substitutions initiated to reduce costs, and unwise assumptions regarding the ability of engineers to solve key technical problems that prevent commercialization of experimental technologies. The detailed discussion of battery, market and photovoltaic materials provides examples of these and other uncertainties.

Currently, efforts to reduce greenhouse gas emissions direct considerable research funding towards electrification of industries. In the short-term, specialty materials used in Nd (Dy)FeB-type magnets are benefiting from rapid market growth due to the increasing popularity of electric vehicles. In the medium- to long-term, the demand for these materials is expected to expand beyond electric vehicles to renewable electricity generation (e.g. turbines for offshore wind farms or tidal/wave energy). The projected demand for electric vehicles will also benefit various materials currently required for the production of Li-ion type batteries. However, the driver for market growth of battery materials will expand to include large-scale stationary electricity storage systems used to balance energy supply and demand, and to provide stability for power grids. These energy storage applications do not require batteries with a high energy density so other types of batteries (e.g. vanadium redox flow) may come to dominate this sector, and these will generate different material requirements.

It is difficult to determine which battery types will become commercially dominant in the long-term or if economically viable substitutes for Nd(Dy)FeB-type magnets will be discovered and commercialized. A single technological breakthrough could abruptly change the situation in both battery and magnet material domains and could significantly alter society's raw material requirements.

The global demand for several specialty materials important in photovoltaic applications is presently satisfied by their recovery as by-products of base metal or other mineral extraction. However, not all smelters have circuits in place to recover materials currently considered as critical. If deficiencies in supplies for materials such as Ge, In, Ga, and other specialty metals develop, adding the appropriate circuits to existing smelting operations may be the most effective way to meet demand.

In the short and medium term, shortages of battery, magnet, and photovoltaic raw materials due to lack of resources are highly unlikely. More likely causes for shortages are supply disruptions linked to civil unrest, military conflicts, supply chain bottlenecks, and delays in permitting future mines and processing facilities for production. Events and uncertainties since early 2020 also provide an illustration of the potential for disruptions from largely unforeseen events such as the Covid-19 pandemic.

#### **CONCLUSION**

In the long term, the ongoing transition from fossil fuels to renewable (alternative) energy sources provides opportunities and potential rewards comparable to the industrial revolution of 1760–1840 in Europe. However, caution is required because (at least in the short term) many critical materials are also specialty materials, used in small quantities compared to major industrial metals such as Fe, Cu, Al, and Zn. This aspect, and the uncertainty related to market projections, must be considered during the planning of exploration and development programs, efforts to secure new supply chains, and in corporate and governmental decision-making.

#### ACKNOWLEDGEMENTS

The motivation to write this paper was sparked by repeated requests for information on 'battery' and 'magnet' materials from Canadian junior exploration companies to the second author while he was science lead of the Specialty Metal Component of the Targeted Geoscience Initiative programs 4 and 5, a collaboration between the Natural Resources Canada and the British Columbia Geological Survey (2010– 2020). A portion of an earlier version of this manuscript benefited from suggestions of Carlee Akam, Dr. Rameses D'Souza, and Connor Robinson from the British Columbia Geological Survey. The final version of this manuscript benefited from comments of reviewer Andrew Bloodworth, British Geological Survey, and editorial suggestions from Andrew Kerr. Copy editing assistance from Robert Raeside and Cindy Murphy at Geoscience Canada was also greatly appreciated.

#### REFERENCES

- Anonymous, 1999, Fuel cells meet big business: Economist, v. 352, no. 8219, p. 59– 60.
- Auerbach, R., Bokelmann, K., Stauber, R., Gutfleisch, O., Schnell, S., and Ratering, S., 2019, Critical raw materials–Advanced recycling technologies and processes: Recycling of rare earth metals out of end of life magnets by bioleaching with various bacteria as an example of an intelligent recycling strategy: Minerals Engineering, v. 134, p. 104–117, https://doi.org/10.1016/ j.mineng.2018.12.022.
- Baker, I., 2018, Rare Earth magnets, *in* Baker, I., *ed.*, Fifty Materials That Make the World: Springer, Cham, p. 187–194, https://doi.org/10.1007/978-3-319- 78766-4.
- Borst, A.M., Smith, M.P., Finch, A.A., Estrade, G., Villanova-de-Benavent, C., Nason, P., Marquis, E., Horsburgh, N.J., Goodenough, K.M., Xu, C. , Kynický, J., and Geraki, K., 2020, Adsorption of rare earth elements in regolith-hosted clay deposits: Nature Communications, v. 11, 4386, https://doi.org/10.1038/ s41467-020-17801-5.
- Braga, A.F.B., Moreira, S.P., Zampieri, P.R., Bacchin, J.M.G., and Mei, P.R., 2008, New processes for the production of solar-grade polycrystalline silicon: A review: Solar Energy Materials and Solar Cells, v. 92, p. 418–424, https://doi.org/10.1016/j.solmat.2007.10.003.
- Brainard, J., Nassar, N.T., Gambogi, J., Baker, M.S., and Jarvis, M.T., 2018, Globally sourced mineral commodities used in U.S. Navy SEAL gear—An illustration of U.S. net import reliance (ver. 2.0, January 2018): U.S. Geological Survey General Information Product 183, https://doi.org/10.3133/gip183.
- Bresser, D., Hosoi, K., Howell, D., Li, H., Zeisel, H., Amine, K., and Passerini, S., 2018, Perspectives of automotive battery R&D in China, Germany, Japan, and the USA: Journal of Power Sources, v. 382, p. 176–178, https://doi.org/ 10.1016/j.jpowsour.2018.02.039.
- Chediak, M., 2018, Big battery boom hits another roadblock: Fire-fearing cities [Technology news]: BloombergQuint, https://www.bloombergquint.com/ technology/the-big-battery-boom-hits-another-roadblock-fire-fearing-cities. Accessed: May 18, 2020.
- Chigondo, F., 2018, From metallurgical-grade to solar-grade silicon: an overview: Silicon, v. 10, p. 789–798*.* https://doi.org/10.1007/s12633-016-9532-7.
- Clarke, G., Northcote, B., Katay, F., and Tombe, S.P., 2021, Exploration and Mining in British Columbia, 2020: A summary: Provincial Overview of Exploration and Mining in British Columbia, 2020, British Columbia Ministry of Energy, Mines and Low Carbon Innovation, Geological Survey Information Circular 2021-01, p. 1–45, http://cmscontent.nrs.gov.bc.ca/geoscience/PublicationCatalogue/InformationCircular/BCGS\_IC2021-01-01.pdf. Accessed: April 5, 2021.
- Cui, J., Kramer, M., Zhou, L., Liu, F., Gabay, A., Hadjipanayis, G., Balasubramanian, B., and Sellmyer, D., 2018, Current progress and future challenges in rare-earthfree permanent magnets: Acta Materialia, v. 158, p. 118–137, https://doi.org/10.1016/j.actamat.2018.07.049.
- Darghouth, A., Aouida, S., and Bessais, B., 2021, High purity porous silicon powder synthesis by magnesiothermic reduction of Tunisian silica sand: Silicon, v. 13, p. 667–676, https://doi.org/10.1007/s12633-020-00433-1.
- Davidsson, S., and Höök, M., 2017, Material requirements and availability for multiterawatt deployment of photovoltaics: Energy Policy, v. 108, p. 574–582, https://doi.org/10.1016/j.enpol.2017.06.028.
- Delfeld, C.T., 2018, How to profit from the commodity market's blind spot: Alquimista Assets Special Report, http://cdn.ceo.ca.s3-us-west-2.amazonaws.com/1ea2dtt-Delfeld-Report-2019.pdf.
- European Commission, 2014, Report on critical raw materials for the EU: Report of the Ad hoc Working Group on defining critical raw materials, 41 p.,

http://litio.ipg.pt/wp-content/uploads/2018/07/EC\_crm-report-on-criticalraw-materials\_2014.pdf. Accessed: August 8, 2021.

- European Commission, 2017, Communication from the Commission to the European Parliament, the Council, the European Economic and Social Committee and the Committee of the Regions on the 2017 list of Critical Raw Materials for the EU: European Commission, Document 52017DC0490, 8 p., https://ec.europa.eu/transparency/regdoc/rep/1/2017/EN/COM-2017-490- F1-EN-MAIN-PART-1.PDF. Accessed: May 15, 2021.
- European Commission, 2018, Report on raw materials for battery applications, 47 p., https://ec.europa.eu/transport/sites/transport/files/3rd-mobility-pac99k/ swd20180245.pdf. Accessed: May 15, 2021.
- European Commission, 2020, Critical raw materials resilience: Charting a path towards greater security and sustainability: Communication from the Commission to the Council, the European Parliament, the European Economic and Social Committee and the Committee of the Regions – Commission of the European Communities – COM 474, Document 52020DC0474, https://eurlex.europa.eu/legal-content/EN/TXT/?uri=CELEX:52020DC0474.
- Evans, K., 2014, Lithium; *in* Gunn, G., *ed.*, Critical Metals Handbook, Chapter 10: John Wiley and Sons, p. 230–260, https://doi.org/10.1002/ 9781118755341.ch10.
- Fishman, T., and Graedel, T.E., 2019, Impact of the establishment of US offshore wind power on neodymium flows: Nature Sustainability, v. 2, p. 332–338, https://doi.org/10.1038/s41893-019-0252-z.
- Flanagan, D.M., 2021, Copper, Mineral Commodity Summaries: United States Geological Survey, p. 52–53, https://pubs.usgs.gov/periodicals/mcs2021/ mcs2021.pdf.
- Fortier, S.M., Nassar, N.T., Mauk, J.L., Hammarstrom, J.M., Day, W.C., and Seal, R.R., 2020, USGS critical minerals review: Mining Engineering, v. 72, p. 30–45.
- Fraunhofer Institute for Solar Energy Systems, 2020, Photovoltaics Report: Fraunhofer ISE, https://www.ise.fraunhofer.de/content/dam/ise/de/documents/ publications/studies/Photovoltaics-Report.pdf. Accessed: March 19.2021.
- Frenzel, M., Mikolajczak, C., Reuter, M.A., and Gutzmer, J., 2017, Quantifying the relative availability of high-tech by-product metals – The cases of gallium, germanium and indium: Resources Policy, v. 52, p. 327–335, https://doi.org/ 10.1016/j.resourpol.2017.04.008.
- Gambogi, J., 2020, Rare Earths, Mineral Commodity Summaries: United States Geological Survey, p. 132–133, https://pubs.usgs.gov/periodicals/mcs2020/ mcs2020.pdf.
- Gambogi, J., 2021a, Rare Earths, Mineral Commodity Summaries: United States Geological Survey, p. 132–133, https://pubs.usgs.gov/periodicals/mcs2021/ mcs2021.pdf.
- Gambogi, J., 2021b, Yttrium, Mineral Commodity Summaries: United States Geological Survey, p. 186–187, https://pubs.usgs.gov/periodicals/mcs2021/ mcs2021.pdf.
- Geuss, M., 2018, Toyota's new magnet won't depend on some key rare-earth minerals [Posted February 28]: Ars Technica, https://arstechnica.com/cars/2018/ 02/neodymium-more-like-neo-dont-mium-new-magnet-uses-fewer-key-rareearths/.
- Goodenough, K.M., Wall, F., and Merriman, D., 2018, The rare earth elements: Demand, global resources, and challenges for resourcing future generations: Natural Resources Research, v. 27, p. 201–216.
- Gourcerol, B., Gloaguen, E., Melleton, J., Tuduri, J., and Galiegue, X., 2019, Reassessing the European lithium resource potential – A review of hard-rock resources and metallogeny: Ore Geology Reviews, v. 109, p. 494–519, https://doi.org/10.1016/j.oregeorev.2019.04.015.
- Government of Canada, 2021, Canada Announces Critical Minerals List: https://www.canada.ca/en/natural-resources-canada/news/2021/03/canadaannounces-critical-minerals-list.html. Accessed: May 15, 2021.
- Green, M.A., Emery, K., Hishikawa, Y., Warta, W., and Dunlop, E.D., 2015, Solar cell efficiency tables (Version 45): Progress in Photovoltaics: Research and Applications, v. 23, p. 1–9, https://doi.org/10.1002/pip.2573.
- Green Car Congress, 2019**,** Adamas: NCM 811 is now the second-most used cathode chemistry in China's passenger EV market [Posted November 15]: BioAge Group LLC, https://www.greencarcongress.com/2019/11/20191115 admas.html. Accessed: July 15, 2021.
- Grunditz, E.A., Lundmark, S.T., Alatalo, M., Thiringer, T., and Nordelöf, A., 2018, Three traction motors with different magnet materials – Influence on cost, losses, vehicle performance, energy use and environmental impact: 2018 Thirteenth International Conference on Ecological Vehicles and Renewable Energies (EVER), p. 1–13, https://doi.org/10.1109/EVER.2018.8362387.
- Guney, M.S., and Tepe, Y., 2017, Classification and assessment of energy storage systems: Renewable and Sustainable Energy Reviews, v. 75, p. 1187–1197, https://doi.org/10.1016/j.rser.2016.11.102.
- Hayes, S.M., and McCullough, E.A., 2018, Critical minerals: A review of elemental trends in comprehensive criticality studies: Resources Policy, v. 59, p. 192–199, https://doi.org/10.1016/j.resourpol.2018.06.015.
- Heath, G.A., Silverman, T.J., Kempe, M., Deceglie, M., Ravikumar, D., Remo, T., Cui, H., Sinha, P., Libby, C., Shaw, S., Komoto, K., Wambach, K., Butler, E., Barnes, T., and Wade, A., 2020, Research and development priorities for silicon photovoltaic module recycling to support a circular economy: Nature Energy, v. 5, p. 502–510, https://doi.org/10.1038/s41560-020-0645-2.
- Höll, R., Kling, M., and Schroll, E., 2007, Metallogenesis of germanium—A review: Ore Geology Reviews, v. 30, p. 145–180, https://doi.org/10.1016/ j.oregeorev.2005.07.034.
- Hummel, P., Lesne, D., Radlinger, J., Golbaz, C., Langan, C., Takahashi, K., Mulholland, D., Stott, A., Haire, G., Mittermaier, M., Gaudois, N., and Shaw, L., 2017, UBS Evidence Lab electric car teardown – Disruption ahead?: Report, UBS Limited, https://neo.ubs.com/shared/d1wkuDlEbYPjF/.
- Hund, K., La Porta, D., Fabregas, T.P., Laing, T., and Drexhage, J., 2020, Minerals for climate action: The mineral intensity of the clean energy transition: World Bank Group, Washington, DC, 112 p., https://pubdocs.worldbank.org/en/ 961711588875536384/Minerals-for-Climate-Action-The-Mineral-Intensity-ofthe-Clean-Energy-Transition.pdf.
- International Energy Agency, 2017, Energy technology perspectives 2017: International Energy Agency Directorate of Sustainability, Technology and Outlooks, 441 p., https://iea.blob.core.windows.net/assets/a6587f9f-e56c-4b1d-96e4- 5a4da78f12fa/Energy\_Technology\_Perspectives\_2017-PDF.pdf. Accessed: May 15, 2021.
- Kesler, S.E., Gruber, P.W., Medina, P.A., Keoleian, G.A., Everson, M.P., and Wallington, T.J., 2012, Global lithium resources: Relative importance of pegmatite, brine and other deposits: Ore Geology Reviews, v. 48, p. 55–69, https://doi.org/10.1016/j.oregeorev.2012.05.006.
- Küpper, D., Kuhlmann, K., Wolf, S., Pieper, C., Xu, G., and Ahmad, J., 2018, The future of battery production for electric vehicles: Boston Consulting Group, September 18, 2018, https://www.bcg.com/en-ca/publications/2018/futurebattery-production-electric-vehicles.aspx.
- Leader, A., Gaustad, G., and Babbitt, C., 2019, The effect of critical material prices on the competitiveness of clean energy technologies: Materials for Renewable and Sustainable Energy, v. 8, 8, https://doi.org/10.1007/s40243-019-0146-z.
- Lin, S.-L., Huang, K.-L., Wang, I.-C., Chou, I-C., Kuo, Y.-M., Hung, C.-H., and Lin, C., 2016, Characterization of spent nickel–metal hydride batteries and a preliminary economic evaluation of the recovery processes: Journal of the Air & Waste Management Association, v. 66, p. 296–306, https://doi.org/10.1080/ 10962247.2015.1131206.
- Louwen, A., van Sark, W., Schropp, R., and Faaij, A., 2016, A cost roadmap for silicon heterojunction solar cells: Solar Energy Materials and Solar Cells, v. 147, p. 295–314, https://doi.org/10.1016/j.solmat.2015.12.026.
- Luo, X., Wang, J., Dooner, M., and Clarke, J., 2015, Overview of current development in electrical energy storage technologies and the application potential in power system operation: Applied Energy, v. 137, p. 511–536, https://doi.org/10.1016/j.apenergy.2014.09.081.
- Mackay, D.A.R., and Simandl, G.J., 2014, Geology, market and supply chain of niobium and tantalum – a review: Mineralium Deposita, v. 49, p. 1025–1047, https://doi.org/10.1007/s00126-014-0551-2.
- Maldonado, S., 2020, The importance of new "sand-to-silicon" processes for the rapid future increase of photovoltaics: ACS Energy Letters, v. 5, p. 3623–3632, https://doi.org/10.1021/acsenergylett.0c02100.
- Marchal, J.C., Krug, D.J., McDonnell, P., Sun, K., and Laine, R.M., 2015, A low cost, low energy route to solar grade silicon from rice hull ash (RHA), a sustainable source: Green Chemistry, v. 17, p. 3931–3940, https://doi.org/10.1039/ c5gc00622h.
- Mariano, A.N., and Mariano Jr., A., 2012, Rare earth mining and exploration in North America: Elements, v. 8, p. 369–376, https://doi.org/10.2113/gselements.8.5.369.
- Mendoza-Vizcaino, J., Raza, M., Sumper, A., Díaz-González, F., and Galceran-Arellano, S., 2019, Integral approach to energy planning and electric grid assessment in a renewable energy technology integration for a 50/50 target applied to a small island: Applied Energy, v. 233–234, p. 524–543, https://doi.org/ 10.1016/j.apenergy.2018.09.109.
- Merli, R., Preziosi, M., and Acampora, A., 2018, How do scholars approach the circular economy? A systematic literature review: Journal of Cleaner Production, v. 178, p. 703–722, https://doi.org/10.1016/j.jclepro.2017.12.112.
- Miao, Y., Hynan, P., von Jouanne, A., and Yokochi, A., 2019, Current Li–ion battery technologies in electric vehicles and opportunities for advancements: Energies, v. 12, 1074, https://doi.org/10.3390/en12061074.
- Millensifer, T.A., Sinclair, W.D., Jonasson, I.R., and Lipmann, A., 2014, Rhenium, *in*

Gunn, G., *ed.*, Critical Metals Handbook, Chapter 14: John Wiley and Sons Ltd., p. 340–360, https://doi.org/10.1002/9781118755341.ch14.

- Nagahata, R., Mori, Y., Saito, Y., Takeuchi, K., Shimizu, Y., Shimizu, M., and Benioub, R., 2021, Efficient carbothermal reduction of diatomaceous earth to silicon using microwave heating: Materials Chemistry and Physics, v. 257, 123744, https://doi.org/10.1016/j.matchemphys.2020.123744.
- Nassar, N.T., 2017, Shifts and trends in the global anthropogenic stocks and flows of tantalum: Resources, Conservation and Recycling, v. 125, p. 233–250, https://doi.org/10.1016/j.resconrec.2017.06.002.
- Oberbeck, L., Alvino, K., Goraya, B., and Jubault, M., 2020, IPVF's PV technology vision for 2030: Progress in Photovoltaics Research and Applications, v. 28, p. 1207–1214, https://doi.org/10.1002/pip.3305.
- Olivetti, E.A., Ceder, G., Gaustad, G.G., and Fu, X., 2017, Lithium-ion battery supply chain considerations: analysis of potential bottlenecks in critical metals: Joule, v. 1, p. 229–243, https://doi.org/10.1016/j.joule.2017.08.019.
- Olson, J., 2021, Graphite (Natural): Mineral Commodity Summaries: United States Geological Survey, p. 72–73, https://pubs.usgs.gov/periodicals/mcs2021/ mcs2021.pdf.
- Paradis, S., 2015, Indium, germanium and gallium in volcanic-and sediment-hosted base-metal sulphide deposits: Symposium on Strategic and Critical Materials Proceedings, November 13–14, 2015, Victoria, British Columbia: British Columbia Ministry of Energy and Mines, Geological Survey Paper, v. 3, p. 23– 29.
- Pavel, C.C., Lacal-Arántegui, R., Marmier, A., Schüler, D., Tzimas, E., Buchert, M., Jenseit, W., and Blagoeva, D., 2017a, Substitution strategies for reducing the use of rare earths in wind turbines: Resources Policy, v. 52, p. 349–357, https://doi.org/10.1016/j.resourpol.2017.04.010.
- Pavel, C.C., Thiel, C., Degreif, S., Blagoeva, D., Buchert, M., Schüler, D., and Tzimas, E., 2017b, Role of substitution in mitigating the supply pressure of rare earths in electric road transport applications: Sustainable Materials and Technologies, v. 12, p. 62–72, https://doi.org/10.1016/j.susmat.2017.01.003.
- Polyak, D.E., 2021, Vanadium: Mineral Commodity Summaries: United States Geological Survey, p. 180–181, https://pubs.usgs.gov/periodicals/mcs2021/ mcs2021.pdf.
- Richter, A., Hermle, M., and Glunz, S.W., 2013, Reassessment of the limiting efficiency for crystalline silicon solar cells: IEEE Journal of Photovoltaics, v. 3, p. 1184–1191, https://doi.org/10.1109/JPHOTOV.2013.2270351.
- Roberts, S., and Gunn, G., 2014, Cobalt, *in* Gunn, G., *ed.*, Critical Metals Handbook, Chapter 6: John Wiley and Sons, p. 122–149, https://doi.org/10.1002/ 9781118755341.ch6.
- Roskill, 2018, Roskill: Neodymium prices surge as permanent magnet demand looks<br>set to take off [Posted January 18]: PR Newswire, set to take off [Posted January 18]: PR Newswire, https://www.prnewswire.com/news-releases/roskill-neodymium-prices-surgeas-permanent-magnet-demand-looks-set-to-take-off-669905463.html.
- Roskill, 2019, Rare earths: Taiwan boosts its offshore wind energy capacity [Posted June 21]: Roskill, https://roskill.com/news/rare-earths-taiwan-boosts-its-offshore-wind-energy-capacity/. Accessed: June 21, 2020.
- Sánchez-Díez, E., Ventosa, E., Guarnieri, M., Trovò, A., Flox, C., Marcilla, R., Soavi, F., Mazur, P., Aranzabe, E., and Ferret, R., 2021, Redox flow batteries: Status and perspective towards sustainable stationary energy storage: Journal of Power Sources, v. 481, 228804, https://doi.org/10.1016/j.jpowsour.2020.228804.
- Sandia National Laboratories, 2020, U.S. Department of Energy Global Energy Storage Database, https://www.sandia.gov/ess-ssl/global-energy-storage-database-home/.
- Sapunkov, O., Pande, V., Khetan, A., Choomwattana, C., and Viswanathan, V., 2015, Quantifying the promise of 'beyond' Li–ion batteries: Translational Materials Research, v. 2, 045002, http://dx.doi.org/10.1088/2053-1613/2/4/045002.
- Schmidt, O., Melchior, S., Hawkes, A., and Staffel, I., 2019, Projecting the future levelized cost of electricity storage technologies: Joule, v. 3, p. 81–100, https://doi.org/10.1016/j.joule.2018.12.008.
- Schnebele, E.K., 2021, Manganese: Mineral Commodity Summaries: United States Geological Survey, p. 104–105, https://pubs.usgs.gov/periodicals/mcs2021/ mcs2021.pdf. Accessed: May 15, 2021.
- Schulze, R., and Buchert, M., 2016, Estimates of global REE recycling potentials from NdFeB magnet material: Resources, Conservation and Recycling, v. 113, p. 12–27, https://doi.org/10.1016/j.resconrec.2016.05.004.
- Schwarz-Schampera, U., 2014, Indium, *in* Gunn, G., *ed.*, Critical Metals Handbook, Chapter 9: John Wiley and Sons, p. 204–229, https://doi.org/10.1002/ 9781118755341.ch9.
- Shi, Y., Eze, C., Xiong, B., He, W., Zhang, H., Lim, T. M., Ukil, A., and Zhao, J., 2019, Recent development of membrane for vanadium redox flow battery applications: A review: Applied Energy, v. 238, p. 202–224. https://doi.org/ 10.1016/j.apenergy.2018.12.087.
- Simandl, G.J., 2014, Geology and market-dependent significance of rare earth ele-<br>ment resources: Mineralium Deposita, v. 49, p. 889–904, ment resources: Mineralium Deposita, v. 49, p. 889–904, https://doi.org/10.1007/s00126-014-0546-z.
- Simandl, G.J., and Paradis, S., 2018, Carbonatites: Related ore deposits, resources, footprint, and exploration methods: Applied Earth Science, v. 127, p. 123–152, https://doi.org/10.1080/25726838.2018.1516935.
- Simandl, G.J., Akam, C., and Paradis, S., 2015, Which materials are 'critical' and 'strategic', *in* Simandl, G.J., and Neetz, M., *eds.*, Symposium on Strategic and Critical Materials Proceedings, November 13–14, 2015, Victoria, British Columbia: British Columbia Ministry of Energy and Mines, Geological Survey Paper 2015-3, p. 1–4.
- Simandl, G.J., Burt, R.O., Trueman, D.L., and Paradis, S., 2018, Economic Geology Models 4. Tantalum and Niobium: Deposits, resources, exploration methods and market-A primer for geoscientists: Geoscience Canada, v. 45, p. 85–96, https://doi.org/10.12789/geocanj.2018.45.135.
- Solar Energy Industries Association, 2018, Solar market insight report 2018 Q3: SEIA/Wood Mackenzie Power & Renewables, https://www.seia.org/researchresources/solar-market-insight-report-2018-q3.
- Swain, N., and Mishra, S., 2019, A review on the recovery and separation of rare earths and transition metals from secondary resources: Journal of Cleaner Production, v. 220, p. 884–898, https://doi.org/10.1016/j.jclepro.2019.02.094.
- U.S. Department of Defense, 2013, Strategic and critical materials 2013 report on stockpile requirements: Office of the Under Secretary of Defense for Acquisition, Technology and Logistics, 189 p., https://mineralsmakelife.org/ assets/images/content/resources/Strategic\_and\_Critical\_Materials\_2013\_Rep ort\_on\_Stockpile\_Requirements.pdf. Accessed: July 15, 2015.
- U.S. Department of Energy, 2011, Critical materials strategy: Office of Policy and International Affairs, 190 p., https://www.energy.gov/sites/prod/files/ DOE\_CMS2011\_FINAL\_Full.pdf.
- U.S. Department of the Interior, 2018, Final list of critical minerals 2018: Federal Register Document Number 2018-10667, v. 83, p. 23296–23297, https://www.govinfo.gov/content/pkg/FR-2018-05-18/pdf/2018-10667.pdf.
- U.S. Geological Survey, 2021, Mineral commodity summaries 2021: U.S. Geological Survey, 200 p., https://doi.org/10.3133/mcs2021.
- Vanýsek, P., and Novák, V., 2017, Redox flow batteries as the means for energy storage: Journal of Energy Storage, v. 13, p. 435–441, https://doi.org/10.1016/ j.est.2017.07.028.
- Verbaan, N., Bradley, K., Brown, J., and Mackie, S., 2015, A review of hydrometallurgical flowsheets considered in current REE projects, *in* Simandl, G.J., and Neetz, M., *eds.*, Symposium on Strategic and Critical Materials Proceedings, November 13–14, 2015, Victoria, British Columbia: British Columbia Ministry of Energy and Mines, Geological Survey Paper 2015-3, p. 147–162.
- Walker, M., 2018, Hype cycles for emerging technologies, 2018 [Posted August 6]: Incorporated, https://www.gartner.com/en/documents/3885468/hype-cycle-for-emergingtechnologies-2018.
- Watts, M., 2010, Shock & ore: The scramble for rare earth self-sufficiency: Industrial Minerals, v. 13, p. 35–41.
- Widmer, J.D., Martin, R., and Kimiabeigi, M., 2015, Electric vehicle traction motors without rare earth magnets: Sustainable Materials and Technologies, v. 3, p. 7– 13, https://doi.org/10.1016/j.susmat.2015.02.001.
- World Bank Group, 2017, The growing role of minerals and metals for a low carbon future: World Bank Group, Washington, DC., 111 http://documents1.worldbank.org/curated/en/207371500386458722/pdf/11 7581-WP-P159838-PUBLIC-ClimateSmartMiningJuly.pdf. Accessed: May 15, 2021.
- Xakalashe, B.S., and Tangstad, M., 2011, Silicon processing: from quartz to crystalline silicon solar cells, *in* Jones, R.T., and den Hoen, P., *eds.*, Southern African Pyrometallurgy 2011: South African Institute of Mining and Metallurgy, Johannesburg, 6–9 March 2011, p. 83–99.
- Zhou, Y., Li, J., Rechberger, H., Wang, G., Chen, S., Xing, W., and Li, P., 2020, Dynamic criticality of by-products used in thin-film photovoltaic technologies by 2050: Journal of Cleaner Production, v. 263, 121599, https://doi.org/ 10.1016/j.jclepro.2020.121599.

**Received June 2021 Accepted as revised July 2021**

## Critical minerals: From discovery to supply chain

## Online workshop, November 16-18

This online workshop will address the critical minerals needed to grow lowcarbon economies, emphasizing those used in battery, magnet, and photovoltaic technologies.

## Register for free via Zoom

https://zoom.us/webinar/register/WN 6mYvDD6bSly5yjD6csXpog



http://cmscontent.nrs.gov.bc.ca/geoscience/ content/2021\_CriticalMineralsWorkshop\_ Preliminary Program.pdf





**Australian Government** Geoscience Australia



Aley niobium-bearing carbonatite, **British Columbia** 



